

Inbound SDS message

†††A†00000076AIRTKTQXREFREQ†02†A^WFRR†S^APPLID%REFCMP†0†0017324162191†1.1%%

| | | | | | | | | | |
|----|-----|-----------|----------------|-----|----|-----------|----|----------|---|
| †† | †A† | †00000076 | AIRTKTQXREFREQ | †02 | †A | ^WFR R | †S | ^APPLID% | REFCMP†0†0017324 1621001732416219 1†1.1%% |
| 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 | 10 |

| | | |
|----|---|---|
| 1 | †† | The SDS Action Code The input message contains the SDS action code †† († = x'86') The “†” is actually a ascii display of the x'86'. The “^” is actually a ascii display of the x'5E'. The “%” is actually a ascii display of the x'89'. |
| 2 | †A† | The SDS Download Action An optional field that identifies the download action for the request follows this (†A†) “A” download action (do you want to send out whole message or blocks), this field can be 'A' or a number 1-16. |
| 3 | †00000076 | Message Length |
| 4 | AIRTKTQXREFREQ | MDR (Message Definition Record. |
| 5 | †02 | Version |
| 6 | †A | Action code indicator |
| 7 | ^WFRR | The Host Application Action Code |
| 8 | †S | S^ the indicator for the Application ID |
| 9 | ^APPLID% | The SDS Application Identifier |
| 10 | REFCMP†0†00173 24162100173241 62191†1.1%% | The MDR Segment and data element information. The actual data is filled in by the SDS user. |

SDS Website: <http://sds.sabre.com/sdsinput.htm>